



GB04/3832



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

REC'D 05 NOV 2004	
WIPO	PCT



Signed *W. Behen*
Dated 21 October 2004

BEST AVAILABLE COPY

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

THE PATENT OFFICE

J

- 9 SEP 2003

NEWPORT

1. Your reference P1630

2. Patent application number
(The Patent Office will fill in this part)

0321005.1

09SEP03 E835865-1 C19381
P01/7780 0.00-0321005.1

3. Full name, address and postcode of the or of each applicant (underline all surnames)

SINGLETON Mark James
Startlink Systems Ltd
Sizecroft
Kilpeck
Hereford HR2 9DW

Patents ADP number (if you know it)

579793/002

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

Structural couplings

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MacLeod Allsop
Bledington Grounds
Bledington
Gloucestershire OX7 6XL

Patents ADP number (if you know it)

745468/001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d)

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s) 2

Abstract None

Drawing(s) 4

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)


Request for substantive examination (Patents Form 10/77)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date



8/09/83

12. Name and daytime telephone number of person to contact in the United Kingdom

JOHN R ALLSOP

01608 659836

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

STRUCTURAL COUPLINGS

5 FIELD OF THE INVENTION

The present invention relates to structural couplings for forming a variety of structures such as floor and wall panels for buildings and internal structures such as hand rails.

BACKGROUND OF INVENTION

10

Unistrut channels for forming a variety of structures are well known.

15

The Unistrut system employs channel sections made exclusively of steel which vary only in overall profile height and the thickness of the steel used. Each Unistrut channel in practice is available alone or welded to one or more pieces of the same section in various arrangements or to thin continuous steel plate to present a varied range of steel structural profiles to which blind connections can be made using Unistrut nuts and screws.

20

A range of flat and folded, pre-drilled steel plates are available with the Unistrut system to connect channels together in different ways to create frame structures.

Fittings are also available so that channels can provide support for cable trays or pipes.

25

Unistrut channels are generally left open between connections although a flat faced closure strip is available. This is the only continuous section that is available to Unistrut channels but is not itself channel shaped and is not used to make connections.

30

Unistrut channels are also used to create truss frames and space frames to which blind attachments can be made:

While the Unistrut system is used to make frames and not continuous surfaces it can be used to provide support for them.

35

Unistrut nuts only fit a range of Unistrut channels which are available in appropriate shapes and are too rigid to be made to enclose another profile.

A problem with the Unistrut system is its limited use in terms of the structures that can be produced in practice for the reasons explained above.

SUMMARY OF THE INVENTION

5 An object of the invention is to realise the possibility of avoiding the need to connect similar profiles to each other to make frames as in the Unistrut system, but rather to connect the profiles together through the intermediary of a common channel profile. In this way two panels for example can be joined, not directly to each other but to a separate profile to which the common channel connects thereby to facilitate the construction, for example, of a continuous wall with
10 reinforcing struts at every join and to which blind fixings can be made.

According to the invention there is provided a structural coupling comprising a structural component or components provided with coupling leg formations and locking flanges on at least a
15 pair of opposing ones of said leg formations in assembly, a connecting channel section the sides of which are adapted respectively to engage said pair of leg formations, a locking formation on the channel section, and a clip fixing for snap fit engagement with said locking formation and said locking flanges to secure the component or components together.

20 Advantageously the leg formations are provided with coupling slots such that when two leg formations on the structural component or components are in opposed relationship the sides of the channel section slot into the respective coupling slots.

The coupling in accordance with the invention may be used to form a floor or roof of a structure.
25 In this case preferably the structural components are in the form of rigid panels assembled in side by side relationship with a leg formation along one edge of a panel in opposed relation to a leg formation on the adjoining panel. The coupling slots preferably are so formed that with the sides of the channel section engaged therein the base of the channel section and the rigid panels lie in the same plane.

30 Other features and advantages of the present invention will become apparent from the following description of a preferred embodiment of the invention taken with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the invention and to show how the same may be carried into effect, reference will now be made by way of example, to the accompanying drawings in which:

Figure 1 is a cross sectional view of a structural coupling in accordance with the invention in the form of a floor panel;

Figure 2 is a cross sectional view of a further structural coupling employing the invention to form a wall panel;

Figure 3 illustrates the use of the invention as a structural coupling in the form of a handrail and;

Figure 4 illustrates the installation of a blind fixing in the structural coupling of Figure 2.

PREFERRED EMBODIMENTS OF THE INVENTION

Figure 1 shows the invention used to connect together two floor panels 1 which may be of varying width or length to suit requirements.

The panels 1 have rigidising pairs of opposed L-shaped legs 2 spaced at intervals along the underside surface of the panel 1 to form open box structures 3.

The opposed edges of the panels 1 are provided with coupling slots 4.

The coupling slots 4 are formed from a short vertically depending wall portion 5 of the panels 1 and the upper vertical extent 2' of an end leg 2 of the panels 1 which is spaced from the short wall portion 5 by a short horizontal wall section 7 which forms the base of the coupling slots 4. The vertical extent 2' of the end leg 2 is provided with an intumed looking flange F provided with a locking rib formation R.

The downward vertical extent of the end leg 2 from the short horizontal wall section 7 forming the base of each of the coupling slots 4, is equal to the vertical extent of the legs 2, while the upward extent 2' is less than that of the short vertically extending wall portions 5 by a distance equal to the thickness of the floor panels 1.

The walls of a channel section 8 respectively engage the coupling slots 4 of two opposing floor panels 1 as shown, the thickness of the base of the channel section 8 being equal to the difference between the length of the walls (2', 5) of the coupling slots 4 thereby to form a continuous flat surface across the join between the two floor panels 1.

5

The base of the channel section 8 is provided with an embossment 9 providing two projecting formations 10 to either side of the centre line of the embossment 9, the projections 10 defining at their rearward extent, channel recesses 11 in the base of the channel section 8 as shown.

10

A snap fit fixing 12 formed by extrusion, is then used to anchor the channel section 8 in the coupling slots 4, the snap fit fixing 12 having flexible barbs 13 which engage the channel recesses 11 and the rib formation R as shown to hold the channel section 8 in a vice like grip in the coupling slots 4.

15

The wall panel as shown in Figure 2 uses the channel section 8 in the same manner as described with reference to Figure 1.

In Figure 2 the channel section 8 is used to complete the assembly of a wall strut for a wall panel.

20

The wall panel is formed of a series of rigid flat panels 14 having side edge leg formations 15, the ends of which have circular recesses 16 for accommodating sealing gaskets 17 as shown.

The wall strut is in the form of a doubled wall channel 18, the space between the double walls forming coupling slots 19.

25

The inner wall leg formations L of the double walled channel 18 are provided with intumed locking flanges F' defining locking ribs R'.

30

The leg formations 15 on the side edges of the wall panels 14 together with the side walls of the channel section 8 are accommodated in tight fit relationship in the coupling slots 19 of the channel shaped wall strut 18, with the sealing gasket 17 in pressure contact with the inner wall leg formation L of the channel 18.

35

As with the Figure 2 embodiment the snap fit fixing 12 is then used to anchor the channel section 8 in the coupling slots 19 by engagement of the flexible barbs 13 which engage the channel recesses 11 and the rib formation R' to hold the channel section 8 together with the leg formations L on the edges of the wall panels in vice like grip in the coupling slots 19.

As shown the design is such that in assembly the outer base wall of the channel section 8 lies in the same plane as the outer surface of the wall panel to provide a continuous finish to the assembly.

The invention may also be used to construct a rail such as a hand rail as shown in Figure 3.

The hand rail 20 is essentially a U profile 21 that is closed by the common channel section 8 in accordance with the invention, around an inner tubular core 22 as shown. This allows the fabricator to make joins in the hand rail or connect to a suitable corner section which can be fixed at any angle.

To effect closure of the rail 20 the ends of the U profile 21 thereof are provided with leg formations E similar to the leg formations 2' and L of the Figure 1 and 2 embodiments and provided with inturned locking flanges F" and locking ribs R".

The internal size of the channel section 8 is such that when the leg formations E are located in the channel section 8 as shown, they are forced together by the walls of the channel section 8 to close the profile 21 around the core 22.

The coupling thus formed is securely held together by means of the clip fixing 12 and inter engaging barbs 13 respectively with the ribs R" and projections 10 as with the Figures 1 and 2 embodiments.

To each of the Figures 1 to 3 embodiments blind fixings can readily be made as illustrated clearly in Figure 4 described with reference to the wall strut assembly of Figure 2.

The blind fixing comprises a locking nut 23 which bridges or spans the locking ribs R' to occupy the space between the walls of the channel section 8. The nut 23 is engaged by a threaded bolt 24 passing through the base of the section 8, the nut 23 having grooves 25 which receive the ribs R' when the bolt 24 is fully engaged. The tension spring 25 is employed to facilitate easy assembly of the nut 23.

In all three embodiments as described it will be observed that each structural coupling employs the use of a common channel section 8 which respectively produces an elegant and non-limiting method of joining structural components together than in a direct fashion as with the Unistrut system.

This is clearly shown in Figure 1 where the common channel section 8 is used to produce a floor panel with a flat continuous surface across the join to which blind fixings can be made, and in Figure 2 where it is used to close the channel form of another profile thereby to entrap a third profile to make a continuous wall with reinforcing struts at every join and to which blind fixings can be made.

Finally the common channel section 8 can be used to close an open profile 21 as shown in Figure 3, and can be formed around an inner profile 16 to form joins in a hand rail.

The constructions as described herein are preferably made by pultrusion.

Pultrusion is a process using machines to produce fibre reinforced polymer profiles. They are lighter and corrosion resistant but more flexible than steel.

Pultrusion profiles have developed a market by imitating steel profiles and offer a range of standard flats, angles, channels, I beams and tubes.

Custom variations include floor and wall panels that provide continuity by overlapping adjacent panels or by using an integral tongue and grooved joint.

Cutting and joining square tubed profiles have produced handrails but these lack the variety produced by bending and welding steel. Pultrusions cannot be welded and connections tend to be made using nuts and bolts blind rivets or adhesives.

With the present invention these deficiencies in pultrusion processing are overcome using the common channel section connector 8 as described with reference to the preferred embodiments described herein.

7
CLAIMS

1. A structural coupling comprising a structural component or components provided with coupling leg formations and locking flanges on at least a pair of opposing ones of said leg formations in assembly, a connecting channel section the sides of which are adapted respectively to engage said pair of leg formations, a locking formation on the channel section, and a clip fixing for snap fit engagement with said locking formation and said locking flanges to secure the component or components together.
2. A structural coupling as claimed in claim 1 wherein the leg formations are provided with coupling slots, such that when said pair of leg formations are in opposed relationship the sides of the channel section engage the respective coupling slots.
3. A structural coupling as claimed in claim 2 wherein said opposed pair of leg formations are on the side edges of a series of rigid sheets or panels disposed in side by side relationship to form part of a structure such as a floor or roof, the sides of the channel section being accommodated in the coupling slots such that the base wall of the channel section and the rigid sheets or panels lie in the same plane.
4. A structural coupling as claimed in claim 2 wherein a said pair of leg formations form the inside walls of a doubled walled channel shaped strut, said coupling slots being formed between said inside walls to receive the side walls of said connecting channel section together with the leg formations formed on the side edges of a series of rigid panels or sheets disposed in side by side relationship to form part of a structure such as a wall panel.
5. A structural coupling as claimed in claim 1 wherein said structural component comprises a longitudinally split rail with the leg formations formed on the side edges of the split, the leg formations being held within said channel section respectively in abutment with opposing internal walls thereof so acting to close the split rail and secure the rail to an inner profile core.
6. A structural coupling as claimed in any preceding claim wherein said locking formation on the channel section is formed on the inside face of the base of the channel section.
7. A structural coupling as claimed in claim 6 wherein said locking formation is comprised of an embossment to provide a pair of channel recesses along the channel base.

8. A structural coupling as claimed in claim 7 wherein said locking flanges on said pair of opposing ones of said leg formations include intumed edges forming locking ribs, said clip fixing having flexible barbs for respective snap fit engagement with said locking ribs and channel recesses to lock the coupling together.

- 5 9. A structural coupling substantially as herein described before with reference to and as illustrated in the accompanying drawings.




FIGURE 2




FIGURE 3

PCT/GB2004/003832

